



Longevity and Easy Maintenance

Certifications, labels,
guarantees & recycling

ISO 9001
ISO 14001

15-year
warranty



IZZITENT

COATED 450GSM, 1000*1000, 2.5*450

Longevity and Easy Maintenance

Main applications

- Covered outdoors
- Sport hall roofs
- Shading structures

Major advantages

- Long lasting and low maintenance
- Controlled color pertranslucency
- High dimensional stability

Technical Data Sheet

Product Name	Base Fabric Density	Widt(m)	Weight g/m ²	Surface	Application
IZZI Tent 450 Coated	1000D*1000D 3*3	2,5	450	Semi Glossy	Tent
Testing item		Testing standard		Result	
Weight		g/m ²		450	
Thickness		mm		0,45	
Tensile strength (N/5cm)	Warp	GB/T13022-1991		637,1	
	Weft			589,3	
Tearing Strength (N/5cm)	Warp	HG/T2581-1994		80,1	
	Weft			185	
Peeling Strength (N/5cm)	Warp	GB/T8808-1998		76,4	
	Weft			89,3	
Flame Retardancy	Extinguish/s	GB/T 5455-1997		--	

The buyer of our products is fully responsible for their application and their transformation with regard to any possible third party. The buyer of our products is responsible for their implementation and installation according to the standards, workmanship and safety regulations in force in destination countries. For information on our contractual warranty, please refer to the relevant terms and conditions. The values quoted above represent results of tests performed in compliance with common design practices and are provided for information only to enable customers to make the best use of our products. Our products are subject to changes based on technical advances and we reserve the right to modify their characteristics at any time. The buyer of our products is responsible for checking the validity of the above data.



Komplek Pergudangan Prima Centre 1,
Extension G no.6, Jakarta Barat -11710,
Indonesia
Tel: 6221-29030985 (hunting),
Fax: 6221-29030986,
email: info@bahterasuksesgemilang.com